

SAFETY DATA SHEET
according to Regulation (EU) 2015/830

Page 1/9

Clearwinner AMAC - MP Fuel Enhancer

Revision 11

Revision date 2018-07-12

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name	Clearwinner AMAC - MP Fuel Enhancer
Product code	QAFS671

1.2. Relevant identified uses of the substance or mixture and uses advised against

Product Use	[SU22] Professional uses: Public domain (administration, education, entertainment, services, craftsmen); ----- [SU21] Consumer uses: Private households (= general public = consumers);
Description	Disperses water, protects fuel system and adds lubricity.

1.3. Details of the supplier of the safety data sheet


Company	Clearwinner Innovation Ltd
Address	Unit 2 Hastings Court Collingham Wetherby West Yorks LS22 5AW
Telephone	07595221498
Email	sales@clear-winner.co.uk
Email address of the competent person	sales@clear-winner.co.uk

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

2.1.2. Classification - EC 1272/2008	: EUH066; Flam. Liq. 3: H226; Asp. Tox. 1: H304; Skin Irrit. 2: H315; Eye Irrit. 2: H319; STOT SE 3: H335; STOT SE 3: H336; Aquatic Chronic 2: H411;
---	--

2.2. Label elements

Hazard pictograms	
Signal Word	Danger
Hazard Statement	EUH066 - Repeated exposure may cause skin dryness or cracking. Flam. Liq. 3: H226 - Flammable liquid and vapour. Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways. Skin Irrit. 2: H315 - Causes skin irritation. Eye Irrit. 2: H319 - Causes serious eye irritation. STOT SE 3: H335 - May cause respiratory irritation. STOT SE 3: H336 - May cause drowsiness or dizziness. Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.

Clearwinner AMAC - MP Fuel Enhancer

Revision 11
Revision date 2018-07-12

2.2. Label elements

Precautionary Statement: Prevention	P102 - Keep out of reach of children. P280 - Wear protective gloves/protective clothing/eye protection/face protection.
Precautionary Statement: Response	P301+P310+P330+P331 - IF SWALLOWED: Immediately call a POISON CENTER/doctor. Rinse mouth. Do NOT induce vomiting. P302+P352 - IF ON SKIN: Wash with plenty of water/ . P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Precautionary Statement: Storage	P403+P233+P235 - Store in a well-ventilated place. Keep container tightly closed. Keep cool.
Precautionary Statement: Disposal	P501 - Dispose of contents/container to an approved disposal site, in accordance with local regulations.

2.3. Other hazards

Other hazards	PBT not identified as a PBT substance.
----------------------	--

SECTION 3: Composition/information on ingredients

3.2. Mixtures

EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification
2-butoxyethanol	603-014-00-0	111-76-2	203-905-0	01-2119475108-36	40 - 50%	Acute Tox. 4: H332; Acute Tox. 4: H312; Acute Tox. 4: H302; Eye Irrit. 2: H319; Skin Irrit. 2: H315;
Hydrocarbons, C9, Aromatics			918-668-5	01-2119455851-35	30 - 40%	: EUH066; Flam. Liq. 3: H226; Asp. Tox. 1: H304; STOT SE 3: H335; STOT SE 3: H336; Aquatic Chronic 2: H411;
o-xylene	601-022-00-9	95-47-6	202-422-2		0.5 - 1%	Flam. Liq. 3: H226; Acute Tox. 4: H332; Acute Tox. 4: H312; Skin Irrit. 2: H315;
dimethylcyclohexylamine		98-94-2	202-715-5		0.5 - 1%	Flam. Liq. 3: H226; Acute Tox. 4: H302; Acute Tox. 3: H311+H331; Skin Corr. 1B: H314;
ethylbenzene	601-023-00-4	100-41-4	202-849-4	01-2119892111-44	0 - 0.5%	Flam. Liq. 2: H225; Acute Tox. 4: H332;
2-ETHYLHEXYL NITRATE		27247-96-7	248-363-6	01-2119539586-27	1 - 10%	EUH044; : EUH066; Acute Tox. 4: H302+H312+H332; Aquatic Chronic 2: H411;

Further information

Product Shelf Life	RECOMMENDED SHELF LIFE 1 YEAR FROM DATE OF DELIVERY.
---------------------------	--

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Move the exposed person to fresh air.
Eye contact	Rinse immediately with plenty of water. Contact lenses should be removed.
Skin contact	Remove contaminated clothing. Wash with water and soap as a precaution.
Ingestion	DO NOT INDUCE VOMITING. Rinse mouth thoroughly.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation	High concentration of vapour in enclosed space may cause irritation, headaches and nausea. May cause irritation to respiratory system. May cause drowsiness or dizziness.
Eye contact	Causes serious eye irritation.
Skin contact	Causes skin irritation. May cause skin dryness and irritation. Prolonged contact may cause

Clearwinner AMAC - MP Fuel Enhancer

Revision 11
Revision date 2018-07-12**4.2. Most important symptoms and effects, both acute and delayed**

Ingestion	defatting of the skin.
	May cause irritation to mucous membranes.

4.3. Indication of any immediate medical attention and special treatment needed

Inhalation	TREAT SYMPTOMATICALLY.
	Move the exposed person to fresh air. Seek medical attention if irritation or symptoms persist.
Eye contact	Contact lenses should be removed. Rinse immediately with plenty of water. Seek medical attention if irritation or symptoms persist.
Skin contact	Seek medical attention if irritation or symptoms persist.
Ingestion	Drink 1 to 2 glasses of water. Seek medical attention if irritation or symptoms persist.

General information

	If you feel unwell, seek medical advice (show the label where possible). Treat symptomatically.
--	---

SECTION 5: Firefighting measures**5.1. Extinguishing media**

	Flammable liquid. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
--	---

5.2. Special hazards arising from the substance or mixture

	Burning produces irritating, toxic and obnoxious fumes.
--	---

5.3. Advice for firefighters

	Wear suitable respiratory equipment when necessary.
--	---

Further information

	In the event of a fire and/or explosion do not breath fumes. Standard procedure for chemical fires. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
--	---

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

	Wear suitable protective equipment. Flammable liquid. Avoid sparks, flames, heat and sources of ignition.
--	---

6.2. Environmental precautions

	Advise local authorities if large spills cannot be contained.
--	---

6.3. Methods and material for containment and cleaning up

	Absorb with inert, absorbent material. Sweep up. Transfer to suitable, labelled containers for disposal. Avoid sparks, flames, heat and sources of ignition.
--	--

6.4. Reference to other sections

	See section 2, 7, 8, 13 for further information.
--	--

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

	Adopt best Manual Handling considerations when handling, carrying and dispensing.
--	---

7.2. Conditions for safe storage, including any incompatibilities

	Flammable liquid. Avoid sparks, flames, heat and sources of ignition. Avoid storing in direct Sun Light. Store in a well-ventilated place. Keep cool. Store in original container. Keep container tightly closed. Keep away from combustible material. Keep out of the reach of children.
--	---

7.3. Specific end use(s)

	No data is available on this product.
--	---------------------------------------

Clearwinner AMAC - MP Fuel Enhancer

Revision 11

Revision date 2018-07-12

Suitable packaging

Plastic containers.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure controls.

8.1.1. Exposure Limit Values

2-butoxyethanol	WEL 8-hr limit ppm: 25 WEL 15 min limit ppm: 50 WEL 8-hr limit mg/m3 total - inhalable dust: WEL 8-hr limit mg/m3 total - respirable dust:	WEL 8-hr limit mg/m3: 123 WEL 15 min limit mg/m3: 101.2 WEL 15 min limit mg/m3 total - inhalable dust: WEL 15 min limit mg/m3 total - respirable dust:
2-ETHYLHEXYL NITRATE	WEL 8-hr limit ppm: WEL 15 min limit ppm: 1 WEL 8-hr limit mg/m3 total - inhalable dust: WEL 8-hr limit mg/m3 total - respirable dust:	WEL 8-hr limit mg/m3: WEL 15 min limit mg/m3: WEL 15 min limit mg/m3 total - inhalable dust: WEL 15 min limit mg/m3 total - respirable dust:
ethylbenzene	WEL 8-hr limit ppm: 100 WEL 15 min limit ppm: 125 WEL 8-hr limit mg/m3 total - inhalable dust: WEL 8-hr limit mg/m3 total - respirable dust:	WEL 8-hr limit mg/m3: 441 WEL 15 min limit mg/m3: 552 WEL 15 min limit mg/m3 total - inhalable dust: WEL 15 min limit mg/m3 total - respirable dust:

DNEL: Derived no-effect level.

Exposure Pattern - Workers

2-butoxyethanol	Acute inhalation - Systemic effects 1091 mg/m ³ Acute inhalation - Local effects 246 mg/m ³ Long-term - inhalation - Systemic effects 98 mg/m ³	Acute dermal - Systemic effects 89 mg/kg Long-term - dermal - Systemic effects 125 mg/kg
2-ETHYLHEXYL NITRATE	Long-term - inhalation - Systemic effects 0.35 mg/m ³ Long-term - dermal - Systemic effects 1 mg/kg	Long-term - dermal - Local effects 0.044 mg/cm ³

Exposure Pattern - General population

2-butoxyethanol	Acute inhalation - Systemic effects 426 mg/m ³ Acute dermal - Systemic effects 89 mg/kg Long-term - inhalation - Systemic effects 59 mg/m ³ Long-term - dermal - Systemic effects 75 mg/kg	Acute oral - Systemic effects 26.7 mg/kg Long-term - inhalation - Local effects 147 mg/m ³ Long-term - oral - Systemic effects 6.3 mg/kg
2-ETHYLHEXYL NITRATE	Long-term - inhalation - Systemic effects 0.087 mg/m ³ Long-term - dermal - Systemic effects 0.52 mg/kg Long-term - oral - Systemic effects 0.025 mg/kg	Long-term - dermal - Local effects 0.022 mg/cm ³

8.2. Exposure controls

Clearwinner AMAC - MP Fuel Enhancer

Revision 11
Revision date 2018-07-12

8.2. Exposure controls



Adopt best Manual Handling considerations when handling, carrying and dispensing. Avoid contact with skin and eyes. Handle in accordance with good industrial hygiene and safety practice. Use appropriate personal protective equipment. Wear suitable protective clothing and eye/face protection.

8.2.1. Appropriate engineering controls

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapours below their respective threshold limit value. Ensure eyewash stations and safety showers are close to the workstation location.

Eye / face protection

Avoid contact with eyes. If splashes are likely to occur, wear: safety glasses with side-shields.

Skin protection - Handprotection

Rubber gloves.

Respiratory protection

No personal respiratory protective equipment normally required. In case of insufficient ventilation wear suitable respiratory equipment.

8.2.3. Environmental exposure controls

Prevent further leakage or spillage if safe to do so.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Liquid
Colour	Clear
Odour	Aromatic
Flash point	50 °C
Evaporation rate	0.15 g/min
Flammability (solid, gas)	No data available
Vapour pressure	No data available
Vapour density	No data available
Relative density	0.9 (H ₂ O = 1 @ 20 °C)
Partition coefficient	No data available
Autoignition temperature	No data available
Viscosity	No data available
Explosive properties	No data available
Oxidising properties	No data available
Odour threshold	No data available
pH	No data available
Melting point	No data available
Initial boiling point	181 °C
Solubility	No data available

9.2. Other information

Conductivity	No data available
Surface tension	No data available
Gas group	No data available
Benzene Content	Not applicable.
Lead content	Not applicable.
VOC (Volatile organic compounds)	Not applicable.

SECTION 10: Stability and reactivity

Clearwinner AMAC - MP Fuel Enhancer

Revision 11
Revision date 2018-07-12

10.1. Reactivity

	Flammable liquid. Stable under normal conditions.
--	---

10.2. Chemical stability

	Flammable liquid. Stable under normal conditions.
--	---

10.3. Possibility of hazardous reactions

	Oxidising agents. Combustible materials.
--	--

10.4. Conditions to avoid

	Avoid sparks, flames, heat and sources of ignition. Avoid storing in direct Sun Light.
--	--

10.5. Incompatible materials

	Oxidising agents.
--	-------------------

10.6. Hazardous decomposition products

	No Hazardous decomposition products when stored and handled correctly. Burning produces irritating, toxic and obnoxious fumes.
--	--

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity	This mixture has not been tested as a whole for health effects. The health effects have been calculated using the methods outlined in Regulation (EC) No 1272/2008 (CLP). based on available data the classification criteria are not met.
Skin corrosion/irritation	Skin Irrit. 2: H315 - Causes skin irritation.
Serious eye damage/irritation	Eye Irrit. 2: H319 - Causes serious eye irritation.
Respiratory or skin sensitisation	based on available data the classification criteria are not met.
Germ cell mutagenicity	based on available data the classification criteria are not met.
Carcinogenicity	based on available data the classification criteria are not met.
Reproductive toxicity	based on available data the classification criteria are not met.
STOT-single exposure	STOT SE 3: H335 - May cause respiratory irritation. STOT SE 3: H336 - May cause drowsiness or dizziness.
STOT-repeated exposure	based on available data the classification criteria are not met.
Aspiration hazard	Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.

11.1.2. Mixtures

	No data available.
--	--------------------

11.1.3. Hazard Information

	No data available.
--	--------------------

11.1.4. Toxicological Information

2-ETHYLHEXYL NITRATE	Dermal Rat LD50: 1111 mg/kg Inhalation Rat LC50/4 h: 11.11 mg/l	Oral Rat LD50: 505.05 mg/kg
-----------------------------	--	------------------------------------

SECTION 12: Ecological information

12.1. Toxicity

2-butoxyethanol	EC50 for marine or freshwater organisms >100.0000 mg/l	LC50 for marine or freshwater organisms >100.0000 mg/l
2-ETHYLHEXYL NITRATE	Daphnia EC50/48h: 12.6000 mg/l Algae EC50/72h: 0.8 mg/l	Fish LC50/96h: 1.8800 mg/l Rainbow trout LC50/96h: 145 mg/l

12.2. Persistence and degradability

	Substance biodegrades at a moderate rate and inherently biodegradable according to the OECD
--	---

Clearwinner AMAC - MP Fuel Enhancer

Revision 11
Revision date 2018-07-12

12.2. Persistence and degradability

guide lines.

12.3. Bioaccumulative potential

No data is available on this product.

Partition coefficient

Clearwinner AMAC - MP Fuel Enhancer No data available

2-butoxyethanol 0.8 log P

12.4. Mobility in soil

No data is available on this product.

12.5. Results of PBT and vPvB assessment

No data is available on this product.

12.6. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Dispose of waste and residues in accordance with local authority requirements.

General information

Dispose of in compliance with all local and national requirements.

Disposal of packaging

Do NOT reuse empty containers. Empty containers can be sent to landfill after cleaning, if in compliance with local and national regulations.

SECTION 14: Transport information

Hazard pictograms



14.1. UN number

UN1268

14.2. UN proper shipping name

PETROLEUM DISTILLATES. N.O.S.

14.3. Transport hazard class(es)

ADR/RID	3
Subsidiary risk	-
IMDG	3
Subsidiary risk	-
IATA	3
Subsidiary risk	-

14.4. Packing group

Packing group III

14.5. Environmental hazards

Clearwinner AMAC - MP Fuel Enhancer

Revision 11
Revision date 2018-07-12

14.5. Environmental hazards

Environmental hazards	Yes
Marine pollutant	Yes

14.6. Special precautions for user

	No additional special precautions.
--	------------------------------------

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

	Not applicable.
--	-----------------

ADR/RID

Hazard ID	30
Tunnel Category	(D/E)

IMDG

EmS Code	F-E S-E
----------	---------

IATA

Packing Instruction (Cargo)	366
Maximum quantity	220 L
Packing Instruction (Passenger)	355
Maximum quantity	60 L

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulations	<p>REGULATION (EC) No 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.</p> <p>COMMISSION REGULATION (EU) No 453/2010 of 20 May 2010 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.</p>
-------------	--

15.2. Chemical safety assessment

	No information available.
--	---------------------------

SECTION 16: Other information

Other information

Revision	<p>This document differs from the previous version in the following areas:.</p> <ul style="list-style-type: none"> 2 - Precautionary Statement: Prevention. 2 - Precautionary Statement: Response. 2 - Precautionary Statement: Storage. 2 - Precautionary Statement: Disposal. 4 - Inhalation. 4 - Eye contact. 4 - Skin contact. 11 - 11.1.4. Toxicological Information. 11 - Skin corrosion/irritation. 11 - 11.1. Information on toxicological effects. 11 - Serious eye damage/irritation.
----------	--

Clearwinner AMAC - MP Fuel Enhancer

Revision 11

Revision date 2018-07-12

Other information

	<p>11 - STOT-single exposure. 11 - Aspiration hazard. 12 - 12.1. Toxicity. 16 - Data sources.</p>
Data sources	<p>Classification and Procedure used to derive the classification for mixtures according to Regulation (EC) No. 1272/2008:.</p> <p>Flam. Liq. 3: H226 - Flammable liquid and vapour. - Flash Point - 50 degC. Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways. - Calculation Method. Skin Irrit. 2: H315 - Causes skin irritation. - Calculation Method. Eye Irrit. 2: H319 - Causes serious eye irritation. - Calculation Method. STOT SE 3: H335 - May cause respiratory irritation. - Calculation Method. STOT SE 3: H336 - May cause drowsiness or dizziness. - Calculation Method. Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects. - Calculation Method.</p>
Text of Hazard Statements in Section 3	<p>Acute Tox. 4: H302 - Harmful if swallowed. Acute Tox. 4: H312 - Harmful in contact with skin. Skin Irrit. 2: H315 - Causes skin irritation. Eye Irrit. 2: H319 - Causes serious eye irritation. Acute Tox. 4: H332 - Harmful if inhaled. EUH066 - Repeated exposure may cause skin dryness or cracking. Flam. Liq. 3: H226 - Flammable liquid and vapour. Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways. STOT SE 3: H335 - May cause respiratory irritation. STOT SE 3: H336 - May cause drowsiness or dizziness. Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects. Acute Tox. 3: H311+H331 - Toxic in contact with skin or if inhaled Skin Corr. 1B: H314 - Causes severe skin burns and eye damage. Flam. Liq. 2: H225 - Highly flammable liquid and vapour. EUH044 - Risk of explosion if heated under confinement. Acute Tox. 4: H302+H312+H332 - Harmful if swallowed, in contact with skin or if inhaled</p>
Further information	
	<p>The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.</p>